1984 Subject and Author Index

All of the articles in the 1984 Forest Products Journal, Volume 34, are listed both by subject and by author. The Subject Index is organized according to the FPRS Division and Technical Committee structure.

The Author Index lists senior author entries which give complete information for the article, and coauthor entries which refer back to the senior author.

Reprints of most articles are available at $2 each, minimum $5, plus 10 percent shipping and handling. Bulk rates are also available. When ordering, please give reprint numbers. A check or money order must accompany each order.

FUNDAMENTAL DISCIPLINES DIVISION

Biology

Decay in Mine Timbers. Part III. Species-Independent Stress Grading, M. Chudnoff, W.E. Eslyn, and D.B. McKeever, 3:43-50 (No. 6550).

Effectiveness of Fumigants Against Marine Wood-Borers, G.G. Helsing, R.D. Graham, and M.A. Newbill, 6:61-64 (No. 6680).

Evaluation of Live Oak Submerged Underwater for 50 Years and Proposed for Use in Rebuilding the U.S.S. Constitution, J.E. Winandy, 5:61-63 (No. 6636).

A Tool for Obtaining Large Cores From Standing Trees, J.R. Hamilton, F.C. Cech, and F.L. Ammons, 11/12:33-34 (No. 6679).

Chemistry

Compatibility of Southern Hardwoods With Portland Cement, A.A. Moslemi and Y.T. Lim, 7/8:22-26 (No. 6588).

Curing Characteristics of Wood Particles From Nine Northern Rocky Mountain Species Mixed With Portland Cement, A.D. Hofstrand, A.A. Moslemi, and J.F. Garcia, 2:57-61 (No. 6619).

Reverse Osmosis in the Production of Maple Syrup, P.E. Sendak and M.F. Morselli, 7/8:57-61 (No. 6677).

Physics

Comparison of Moisture Content Distribution, Stress Distribution, and Shrinkage of Red Oak Lumber Dried by a Radio-Frequency/Vacuum Drying Process and a Conventional Kiln, R.A. Harris and M.A. Taras, 1:44-54 (No. 6606).

Effect of Surface Compaction on the Moisture Content of Piled Green Hardwood Chips, M.S. White, M.C. Vodak, and D.C. Cupp, 5:59-60 (No. 6620).

Fuel Values of Stems and Branches in White Oak, Yellow-poplar, and Sweetgum, R.A. Harris, 3:25-26 (No. 6596).

Relative Humidity, EMC, and Collapse Shrinkage in Wood, C.A. Hart, 11/12:45-54 (No. 6671).

Within-Kiln Variability of Transmission Heat Losses, F.L. Laytner and D.G. Arganbright, 2:62-68 (No. 6443).

Wood Engineering & Mechanical Properties

Decay in Mine Timbers. Part III. Species-Independent Stress Grading, M. Chudnoff, W.E. Eslyn, and D.B. McKeever, 3:43-50 (No. 6550).

Deflection Analysis of Shelves and Case Tops and Bottoms, C.A. Eckelman and M. Resheidat, 6:55-60 (No. 6426).

Effect of Loading Rate on Tensile Strength of Douglas-fir 2 by 6's, C.C. Gerhards, C.M. Marx, D.W. Green, and J.W. Evans, 4:23-26 (No. 6593).

Effect of Shock Loading From Series Testing on Tensile Strength of Lumber and Connector Systems, C.C. Gerhards and R.F. Pellerin, 1:38-43 (No. 6578).

Effects of Post-Treatment Drying Schedule on the Strength of CCA-Treated Southern Pine Dimension Lumber, H.M. Barnes and P.H. Mitchell, 6:29-33 (No. 6617).

End Jointing of Laminated Veneer Lumber for Structural Use, J.A. Youngquist, T.L. Laufenberg, and B.S. Bryant, 11/12:25-32 (No. 6664).

Evaluation of Live Oak Submersed Underwater for 50 Years and Proposed for Use in Rebuilding the U.S.S. Constitution, J.E. Winandy, 5:61-63 (No. 6636).

Full-Scale Testing and Structural Evaluation of a Truss-Framed Assembly, L.D. Luttrell and R.L. Tuomi, 1:64-68 (No. 6545).

Holding Strength of Metal Inserts in Wood, C.A. Eckelman and D.L. Cassens, 6:21-25 (No. 6589).

Lateral Resistance of Nailed Joints—A Test Method, J.Y. Liu and L.A. Soltis, 1:55-60 (No. 6582).

Measuring General Slope of Grain With the Slope-of-Grain Indicator, M. Samson, 7/8:27-32 (No. 6682).

Mechanical Tests of Full-Sized Polymer Impregnated Timbers, C.E. Shuler, 6:26-28 (No. 6645).

Minnesota Shear Test Reproducibility and Correlation With Internal Bond, H.J. Hall, J.G. Haygreen, and Y. Lee, 9:49-52 (No. 6660).

Nondestructive Screening of Hardwood Specialty Blanks, M.A. Dean and J.H. Kaiserlik, 3:51-56 (No. 6569).

Physical and Mechanical Properties of Cement Bonded Southern Pine Excelsior Board, A.W.C. Lee, 4:30-34 (No. 6634).

Properties of Red Oak Lumber Dried by Radio-Frequency/Vacuum Process and Dehumidification Process, A.W.C. Lee and R.A. Harris, 5:56-58 (No. 6637).

Static Bending Properties of Structural Wood-Base Panels: Large Panel Versus Small-Specimen Tests, J.D. McNatt, 4:50-54 (No. 6632).

Strength and Stiffness of Red Alder and Bigleaf Maple Pallet Materials, K.M. Bastendorff and A. Polensek, 7/8:51-56 (No. 6489).

MANAGEMENT

Economics & Financial Management

Analyzing a Forest Resource Based Region Facing Economic Change, R.B. Long and G.A. Hines, 10:51-58 (No. 6607).

Changes in Postwar U.S. Lumber Consumption Patterns, H. Spelter and R.B. Phelps, 2:35-41 (No. 6585).

Economic Feasibility of Synthetic Fiber Reinforced Laminated Veneer Lumber (LVL), T.L. Laufenberg, R.E. Rowlands, and G.P. Krueger, 4:15-22 (No. 6604).

Feasibility of Small Mill Investments for Utilizing Small-Diameter Hardwood From Coal Lands in Southwestern Virginia, T.D. McCay and H.W. Wisdom, 6:43-48 (No. 6639).

Floating Exchange Rates and the U.S. Forest Products Trade Balance, H.F. Kaiser, 11/12:55-58 (No. 6678).

Forecasting the Price of Lumber and Plywood: Econometric Model Versus Futures Markets, J. Buongiorno, F.M. Huang, and H. Spelter, 7/8:13-18 (No. 6670).

Hardwood Lumber Demand in the United States: 1950 to 1980, P.A. Cardellichio and C.S. Binkley, 2:15-22 (No. 6562).

How a Forest Products Firm Looks at Eastern Hardwood Opportunities, J.S. Stolley, 10:13-16 (No. 6756).

A Spatial Regional Timber Supply Model For Industrial Expansion, D.W. Rose, A.R. Ek, H.M. Hoganson, and P. Aube, 1:21-27 (No. 6486).

State Income Tax Implications for Nonindustrial Private Forestry in the United States, G.T. McGee, H.L. Haney, Jr., and W.C. Siegel, 3:27-36 (No. 6592).

Marketing

Changes in Postwar U.S. Lumber Consumption Patterns, H. Spelter and R.B. Phelps, 2:35-41 (No. 6585).

Current and Future Demands for Hardwoods, R.B. Phelps, 10:8-11 (No. 6754).

Exporting Southern Softwood Lumber: How Small Firms Can Begin, R.W. Guldin, 3:37-42 (No. 6573).

Hardwood Lumber Demand in the United States: 1950 to 1980, P.A. Cardellichio and C.S. Binkley, 2:15-22 (No. 6562).

How a Forest Products Firm Looks at Eastern Hardwood Opportunities, J.S. Stolley, 10:13-16 (No. 6756).

Marketing Research for Primary Processors of Northern Softwood Lumber, R.L. Govett and S.A. Sinclair, 5:13-20 (No. 6629).

Production Management

Japanese Manufacturing and Management Techniques and the U.S. Forest Products Industry, D. Leding and J.L. Bowyer, 11/12:13-22 (No. 6697).

Merchandiser Design Using Simulation With Graphical Animation, J.L. Garbini, M.R. Lembersky, U.H. Chi, and M.T. Hehnen, 4:61-68 (No. 6618).

Production Rates and Costs of Cable Yarding Wood Residue From Clearcut Units, C.B. LeDoux, 4:55-60 (No. 6603).

Production Rates and Costs of Whole-Tree, Tree-Length, and Log-Length Skyline Thinning, N.E. Putnam, L.D. Kellogg, and E.D. Olsen, 6:65-69 (No. 6656).

Quality Control

Effect of Sweep and Crook on Veneer Yield, J.G. Schroeder and D. R. Phillips, 10:45-47 (No. 6714).

Evaluating Wood Failure in Plywood Shear by Optical Image Analysis, C.W. McMillin, 7/8:67-69 (No. 6690).

Measuring General Slope of Grain With the Slope-of-Grain Indicator, M. Samson, 7/8:27-32 (No. 6682).

Nondestructive Screening of Hardwood Specialty Blanks, M.A. Dean and J.H. Kaiserlik, 3:51-56 (No. 6569).

Random Sampling Process for Improving Lumber Cut-Up Recovery, K.L Nowakowski, 11/12:23-24 (No. 6706).

Technique for Isolating Flakes From the Pressed Mat, A. Jahan-Latibari, W.E. Johns, and R.V. Subramanian, 2:33-34 (No. 6530).

Water Soak Versus Wicking Test for Hardboard Siding, M.W. Kelly, C.A. Hart, and G.F. Laughinghouse, 6:49-54 (No. 6653).

Research Management

Microcomputer Program for Random Selection of Board Samples From Stacked Lumber, D. Bozaan, C.W. Ramm, and M.J. Beauregard, 2:51-52 (No. 6544).

PROCESSES DIVISION

Drying & Storage

Commercial Evaluation of SDR (Saw-Dry-Rip)--Using Aspen for Door Parts, H. Huber, R.R. Maeglin, and D. Bozaan, 11/12:35-39 (No. 6667).

Comparison of Moisture Content Distribution, Stress Distribution, and Shrinkage of Red Oak Lumber Dried by a Radio-Frequency/Vacuum Drying Process and a Conventional Kiln, R.A. Harris and M.A. Taras, 1:44-54 (No. 6606).

Effects of Post-Treatment Drying Schedule on the Strength of CCA-Treated Southern Pine Dimension Lumber, H.M. Barnes and P.H. Mitchell, 6:29-33 (No. 6617).

An Electronic System for Monitoring Gradients of Drying Wood, J.B. Forrer, 7/8:34-38 (No. 6647).

Green Sorting Incense-cedar for Increased Air-Drying Yard Throughput, S. Holmes and D. G. Arganbright, 3:57-63 (No. 6305).

High-Temperature Kiln-Drying of 4/4 Lumber From 12 Hardwood Species, R.S. Boone, 3:10-18 (No. 6584).

Industrial Use of Solar Heat in Lumber Drying: A Long-Term Performance Report, R.L. Little, 9:22-26 (No. 6621).

Maximum Safe Initial Moisture Content for Press-Drying Oak Lumber Without Honeycomb, W. Simpson, 5:47-50 (No. 6622).

Moisture Levels and Gradients in Commercial Softwood Dimension Lumber Shortly After Kiln-Drying, W.L. James, E.T. Choong, D.G. Arganbright, D.K. Doucet, M.R. Gorvad, W.L. Galligan, and W.T. Simpson, 11/12:59-64 (No. 6676).

Obtaining Uniform Final Moisture Content in the High Temperature Drying of Paper Birch Plitches, R.W. Erickson, H.D. Petersen, and T.D. Larson, 2:27-32 (No. 6516).

Practical Drying Techniques for Yellow-poplar S-D-R Plitches, B.R. Weik, E.M. Wengert, J. Schroeder, and R. Brisbin, 7/8:39-44 (No. 6686).

Properties of Red Oak Lumber Dried by Radio-Frequency/Vacuum Process and Dehumidification Process, A.W.C. Lee and R.A. Harris, 5:56-58 (No. 6637).

Relative Humidity, EMC, and Collapse Shrinkage in Wood, C.A. Hart, 11/12:45-54 (No. 6671).

Solar Dry Kiln for Tropical Latitudes, W.T. Simpson and J.L. Tschernitz, 5:25-34 (No. 6580).

Sound Quality Upholstered Frame Part Yields From Lumber and Green Cuttings Dried by a Radio-Frequency/Vacuum System and by Conventional Kiln-Drying, R.A. Harris, M.A. Taras, and J.G. Schroeder, 7/8:19-21 (No. 6646).

Treating and Drying Composite Lumber With Waterborne Preservatives: Part I. Short Specimen Testing, L.I. Gaby and L.R. Gjovik, 2:23-26 (No. 6327).

Within-Kiln Variability of Transmission Heat Losses, F.L. Laytner and D.G. Arganbright, 2:62-68 (No. 6443).

Energy Generation & Conservation

Domestic-Sized Wood Chip Stoker: Combustion and Efficiency, M.H. Schneider, 3:19-24 (No. 6590).

Effect of Fire Retardant Chemicals on Chimney Creosote Deposit, M.M. Nassar and G.D.M. MacKay, 2:53-56 (No. 6542).

Effect of Species and Wood to Bark Ratio on Pelleting of Southern Woods, J. Bradfield and M.P. Levi, 1:61-63 (No. 6554).

Effect of Surface Compaction on the Moisture Content of Piled Green Hardwood Chips, M.S. White, M.C. Vodak, and D.C. Cupp, 5:59-60 (No. 6620).

Fuel Values of Stems and Branches in White Oak, Yellow-poplar, and Sweetgum, R.A. Harris, 3:25-26 (No. 6596).

Wood Fuel Production From Young Piedmont Oak Stands of Sprout Origin, R.A. Harris and R. Zahner, 6:34-38 (No. 6631).

Finishing & Overlaying

Effect of Decorative Vinyl Overlays on Formaldehyde Emissions, W.J. Groah, G.D. Gramp, and M. Trant, 4:27-29 (No. 6602).

Gluing

Curing Characteristics of Wood Particles From Nine Northern Rocky Mountain Species Mixed With Portland Cement, A.D. Hofstrand, A.A. Moslemi, and J.F. Garcia, 2:57-61 (No. 6619).

Effect of Decorative Vinyl Overlays on Formaldehyde Emissions, W.J. Groah, G.D. Gramp, and M. Trant, 4:27-29 (No. 6602).

Effect of Ventilation Rate and Board Loading on Formaldehyde Concentration: A Critical Review of the Literature, G.E. Myers, 10:59-68 (No. 6655).

An Emulsion Polymer/Isocyanate Adhesive for Laminating Composite Lumber, C.B. Vick, 9:27-34 (No. 6598).

End Jointing of Laminated Veneer Lumber for Structural Use, J.A. Youngquist, T.L. Laufenberg, and B.S. Bryant, 11/12:25-32 (No. 6664).

Evaluating Wood Failure in Plywood Shear by Optical Image Analysis, C.W. McMillin, 7/8:67-69 (No. 6690).

Face-Glued Blockboard From Plywood End Trim, D.D. Stokke and J.L. Bowyer, 11/12:40-44 (No. 6687).

Fast-Set Adhesives for Glulam, A. Pizzi and F.A. Cameron, 9:61-68 (No. 6571).

How Mole Ratio of UF Resin Affects Formaldehyde Emission and Other Properties: A Literature Critique, G.E. Myers, 5:35-41 (No. 6628).

Hydrolytic Effects of an Acid-Phenolic Molding Resin on Southern Pine, Red Oak, and Douglas-fir, C.B. Vick, 10:37-44 (No. 6666).

Investigation of Various End Joints in Parallel-Laminated Veneer, J. Jung 5:51-55 (No. 6633).

Preheating Veneer Reduces Press Time in Phenolic-Bonded PLV, R.W. Jokerst, 2:47-50 (No. 6572).

Mechanical Fastening

Effect of Shock Loading From Series Testing on Tensile Strength of Lumber and Connector Systems, C.C. Gerhards and R.F. Pellerin, 1:38-43 (No. 6578).

Holding Strength of Metal Inserts in Wood, C.A. Eckelman and D.L. Cassens, 6:21-25 (No. 6589).

Lateral Resistance of Nailed Joints--A Test Method, J.Y. Liu and L.A. Soltis, 1:55-60 (No. 6582).

Milling & Machining

ALPS--A Potential New Automated Lumber Processing System, C.W. McMillin, R.W. Conners, and H.A. Huber, 1:13-20 (No. 6576).

Analysis of Vibration in a Bandsaw System, W.Z. Wu and C.D. Mote, Jr., 9:12-21 (No. 6745).

Commercial Evaluation of SDR (Saw-Dry-Rip)--Using Aspen for Door Parts, H. Huber, R.R. Maeglin, and D. Bozaan, 11/12:35-39 (No. 6667).

Effect of Chip Freezing on Quality of Ring-Cut Flakes, C.G. Carll and J.E. Wood, 4:35-36 (No. 6624).

Feasibility of Small Mill Investments for Utilizing Small-Diameter Hardwood From Coal Lands in Southwestern Virginia, T.D. McCay and H.W. Wisdom, 6:43-48 (No. 6639).

Latest Developments in Circular Saw Tensioning, R. Szymani and J. Rhemrev, 5:64-68 (No. 6683).

Locating Knots by Industrial Tomography--A Feasibility Study, F.W. Taylor, F.G. Wagner, Jr., C.W. McMillin, I.L. Morgan, and F.F. Hopkins, 5:42-46 (No. 6638).

Lumber Recovery From Gypsy Moth-Killed Red and White Oak Trees, L.D. Garges, P. Labosky, and P.R. Blankenhorn, 7/8:45-50 (No. 6661).

A New Approach to Calculating Target Sizes, S.J. Wang, 9:53-60 (No. 6654).

Resultant Force and Surface Quality From Some Face-Milling Variables, H.A. Stewart, 5:21-24 (No. 6601).

Saw Blade Tooth Wear Reduction by Electrically Insulating the Saw Blade, R.L. Lemaster, 7/8:62-66 (No. 6681).

Sawkerf Width Versus Sawtooth Width, D.W. Patterson, 7/8:33 (No. 6668).

Sound Quality Upholstered Frame Part Yields From Lumber and Green Cuttings Dried by a Radio-Frequency/Vacuum System and by Conventional Kiln-Drying, R.A. Harris, M.A. Taras, and J.G. Schroeder, 7/8:19-21 (No. 6646).

Process Control

Merchandiser Design Using Simulation With Graphical Animation, J.L. Garbini, M.R. Lembersky, U.H. Chi, and M.T. Hehnen, 4:61-68 (No. 6618).

Timber Production & Harvesting

Cable Yarding Residue After Thinning Young Stands: A Break-Even Simulation, C.B. LeDoux, 9:35-40 (No. 6630).

Encouraging Growth and Use of Eastern Hardwoods: Public and Private Programs for the Task, P.V. Ellefson, 10:18-23 (No. 6755).

Mechanized Piling During Pine Plantation Thinning, M.C. Somerville, B.L. Lanford, and B.J. Stokes, 4:45-49 (No. 6605).

Production Rates and Costs of Cable Yarding Wood Residue From Clearcut Units, C.B. LeDoux, 4:55-60 (No. 6603).

Production Rates and Costs of Whole-Tree, Tree-Length, and Log-Length Skyline Thinning, N.E. Putnam, L.D. Kellogg, and E.D. Olsen, 6:65-69 (No. 6656).

Reverse Osmosis in the Production of Maple Syrup, P.E. Sendak and M.F. Morselli, 7/8:57-61 (No. 6677).

Ruminant Feedstuff From the Commercial Foliage of Hybrid Poplars Grown Under Intensive Culture, N.D. Nelson, J.A. Sturos, P.R. Fritschel, and L.D. Satter, 4:37-44 (No. 6599).

State Income Tax Implications for Nonindustrial Private Forestry in the United States, G.T. McGee, H.L. Haney, Jr., and W.C. Siegel, 3:27-36 (No. 6592).

Wood Fuel Production From Young Piedmont Oak Stands of Sprout Origin, R.A. Harris and R. Zahner, 6:34-38 (No. 6631).

PRODUCTS DIVISION

Bark & Residues

Investigations on the Use of Spruce Bark in the Manufacture of Particleboard in Poland, Z. Muszynski and J.D. McNatt, 1:28-35 (No. 6579).

Sawmill Wood Residue for Reclaiming Bentonite Spoils, G.E. Schuman and T.A. Sedbrook, 11/12:65-68 (No. 6721).

Construction Plywood

Effect of Sweep and Crook on Veneer Yield, J.G. Schroeder and D.R. Phillips, 10:45-47 (No. 6714).

Evaluating Wood Failure in Plywood Shear by Optical Image Analysis, C.W. McMillin, 7/8:67-69 (No. 6690).

Face-Glued Blockboard From Plywood End Trim, D.D. Stokke and J.L. Bowyer, 11/12:40-44 (No. 6687).

Forecasting the Price of Lumber and Plywood: Econometric Model Versus Futures Markets, J. Buongiorno, F.M. Huang, and H. Spelter, 7/8:13-18 (No. 6670).

Recovery of Structural Grade Veneer From Four Species of Southern Hardwoods, A. Clark III and R.H. McAlister, 6:13-20 (No. 6609).

Furniture, Millwork, & Allied Products

Deflection Analysis of Shelves and Case Tops and Bottoms, C.A. Eckelman and M. Resheidat, 6:55-60 (No. 6426).

Sound Quality Upholstered Frame Part Yields From Lumber and Green Cuttings Dried by a Radio-Frequency/Vacuum System and by Conventional Kiln-Drying, R.A. Harris, M.A. Taras, and J.G. Schroeder, 7/8:19-21 (No. 6646).

Hardboard & Insulation Board

Physical and Mechanical Properties of Cement Bonded Southern Pine Excelsior Board, A.W.C. Lee, 4:30-34 (No. 6634).

Water Soak Versus Wicking Test for Hardboard Siding, M.W. Kelly, C.A. Hart, and G.F. Laughinghouse, 6:49-54 (No. 6653).

Hardwood Lumber

Alternate Roofing Materials: Grade, Yield, and Costs for Yellow-poplar and Southern Pine Shingles, H.M. Barnes and B. Buchanan, 10:48-50 (No. 6700).

Commercial Evaluation of SDR (Saw-Dry-Rip)—Using Aspen for Door Parts, H. Huber, R.R. Maeglin, and D. Bozaan, 11/12:35-39 (No. 6667).

Comparison of Moisture Content Distribution, Stress Distribution, and Shrinkage of Red Oak Lumber Dried by a Radio-Frequency/Vacuum Drying Process and a Conventional Kiln, R.A. Harris and M.A. Taras, 1:44-54 (No. 6606).

Feasibility of Small Mill Investments for Utilizing Small-Diameter Hardwood From Coal Lands in Southwestern Virginia, T.D. McCay and H.W. Wisdom, 6:43-48 (No. 6639).

Hardwood Lumber Demand in the United States: 1950 to 1980, P.A. Cardellichio and C.S. Binkley, 2:15-22 (No. 6562).

High-Temperature Kiln-Drying of 4/4 Lumber From 12 Hardwood Species, R.S. Boone, 3:10-18 (No. 6584).

Lumber Recovery From Gypsy Moth-Killed Red and White Oak Trees, L.D. Garsee, P. Labosky, and P.R. Blankenhorn, 7/8:45-50 (No. 6661).

Maximum Safe Initial Moisture Content for Press-Drying Oak Lumber Without Honeycomb, W. Simpson, 5:47-50 (No. 6622).

Nondestructive Screening of Hardwood Specialty Blanks, M.A. Dean and J.H. Kaiserlik, 3:51-56 (No. 6569).

Practical Drying Techniques for Yellow-poplar S-D-R Flitches, B.R. Weik, E.M. Wengert, J. Schroeder, and R. Brisbin, 7/8:39-44 (No. 6686).

Random Sampling Process for Improving Lumber Cut-Up Recovery, K.L. Nowakowski, 11/12:23-24 (No. 6706).

Sound Quality Upholstered Frame Part Yields From Lumber and Green Cuttings Dried by a Radio-Frequency/Vacuum System and by Conventional Kiln-Drying, R.A. Harris, M.A. Taras, and J.G. Schroeder, 7/8:19-21 (No. 6646).

Strength and Stiffness of Red Alder and Bigleaf Maple Pallet Materials, K.M. Bastendorff and A. Polensek, 7/8:51-56 (No. 6489).

Laminated Wood, Components, & Engineered Structures

Economic Feasibility of Synthetic Fiber Reinforced Laminated Veneer Lumber (LVL), T.L. Laufenberg, R.E. Rowlands, and G.P. Krueger, 4:15-22 (No. 6604).

Effect of Shock Loading From Series Testing on Tensile Strength of Lumber and Connector Systems, C.C. Gerhards and R.F. Pellerin, 1:38-43 (No. 6578).

An Emulsion Polymer/Isocyanate Adhesive for Laminating Composite Lumber, C.B. Vick, 9:27-34 (No. 6598).

End Jointing of Laminated Veneer Lumber for Structural Use, J.A. Youngquist, T.L. Laufenberg, and B.S. Bryant, 11/12:25-32 (No. 6664).

Fast-Set Adhesives for Glulam, A. Pizzi and F.A. Cameron, 9:61-68 (No. 6571).

Full-Scale Testing and Structural Evaluation of a Truss-Framed Assembly, L.D. Luttrell and R.L. Tuomi, 1:64-68 (No. 6545).

Investigation of Various End Joints in Parallel-Laminated Veneer, J. Jung, 5:51-55 (No. 6633).

Preheating Veneer Reduces Press Time in Phenolic-Bonded PLV, R.W. Jokerst, 2:47-50 (No. 6572).

Treating and Drying Composite Lumber With Waterborne Preservatives: Part I. Short Specimen Testing, L.I. Gaby and L.R. Glovik, 2:23-26 (No. 6327).

Pallets & Containers

Strength and Stiffness of Red Alder and Bigleaf Maple Pallet Materials, K.M. Bastendorff and A. Polensek, 7/8:51-56 (No. 6489).

Particleboard & Molded Products

Compatibility of Southern Hardwoods With Portland Cement, A.A. Moslemi and Y.T. Lim, 7/8:22-26 (No. 6588).

Curing Characteristics of Wood Particles From Nine Northern Rocky Mountain Species Mixed With Portland Cement, A.D. Hofstrand, A.A. Moslemi, and J.F. Garcia, 2:57-61 (No. 6619).

Effect of Chip Freezing on Quality of Ring-Cut Flakes, C.G. Carll and J.E. Wood, 4:35-36 (No. 6624).

Effect of Decorative Vinyl Overlays on Formaldehyde Emissions, W.J. Groah, G.D. Gramp, and M. Trant, 4:27-29 (No. 6602).

Effect of Ventilation Rate and Board Loading on Formaldehyde Concentration: A Critical Review of the Literature, G.E. Myers, 10:59-68 (No. 6655).

Hydrolytic Effects of an Acid-Phenolic Molding Resin on Southern Pine, Red Oak, and Douglas-fir, C.B. Vick, 10:37-44 (No. 6666).

Influence of Natural Durability, Laboratory Weathering, Resin Content, and Ammoniacal Copper Arsenate Treatment on the Decay Resistance of African Hardwood Particleboards, S.P.A. Okoro, R.O. Gertjejansen, and D.W. French, 9:41-48 (No. 6381).

Investigations on the Use of Spruce Bark in the Manufacture of Particleboard in Poland, Z. Muszynski and J.D. McNatt, 1:28-35 (No. 6579).

Minnesota Shear Test Reproducibility and Correlation With Internal Bond, H.J. Hall, J.G. Haygreen, and Y. Lee, 9:49-52 (No. 6660).

Physical and Mechanical Properties of Cement Bonded Southern Pine Excelsior Board, A.W.C. Lee, 4:30-34 (No. 6634).

Spruce Budworm Killed Balsam Fir as a Raw Material for Flakeboard and Waferboard, M. Hughes and R. Gertjejansen, 2:42-46 (No. 6586).

Static Bending Properties of Structural Wood-Base Panels: Large Panel Versus Small-Specimen Tests, J.D. McNatt, 4:50-54 (No. 6632).

Technique for Isolating Flakes From the Pressed Mat, A. Jahan-Latibari, W.E. Johns, and R.V. Subramanian, 2:33-34 (No. 6530).

Residential & Commercial Buildings

Alternate Roofing Materials: Grade, Yield, and Costs for Yellow-poplar and Southern Pine Shingles, H.M. Barnes and B. Buchanan, 10:48-50 (No. 6700).

Softwood Lumber

Alternate Roofing Materials: Grade, Yield, and Costs for Yellow-poplar and Southern Pine Shingles, H.M. Barnes and B. Buchanan, 10:48-50 (No. 6700).

Changes in Postwar U.S. Lumber Consumption Patterns, H. Spelter and R.B. Phelps, 2:35-41 (No. 6585).

Effect of Loading Rate on Tensile Strength of Douglas-fir 2 by 6's, C.C. Gerhards, C.M. Marx, D.W. Green, and J.W. Evans, 4:23-26 (No. 6593).

Effect of Shock Loading From Series Testing on Tensile Strength of Lumber and Connector Systems, C.C. Gerhards and R.F. Pellerin, 1:38-43 (No. 6578).

Effects of Post-Treatment Drying Schedule on the Strength of CCA-Treated Southern Pine Dimension Lumber, H.M. Barnes and P.H. Mitchell, 6:29-33 (No. 6617).

An Emulsion Polymer/Isocyanate Adhesive for Laminating Composite Lumber, C.B. Vick, 9:27-34 (No. 6598).

Exporting Southern Softwood Lumber: How Small Firms Can Begin, R.W. Guldin, 3:37-42 (No. 6573).

Forecasting the Price of Lumber and Plywood: Econometric Model Versus Futures Markets, J. Buongiorno, F.M. Huang, and H. Spelter, 7/8:13-18 (No. 6670).

Marketing Research for Primary Processors of Northern Softwood Lumber, R.L. Govett and S.A. Sinclair, 5:13-20 (No. 6629).

Microcomputer Program for Random Selection of Board Samples From Stacked Lumber, D. Bozaan, C.W. Ramm, and M.J. Beauregard, 2:51-52 (No. 6544).

Moisture Levels and Gradients in Commercial Softwood Dimension Lumber Shortly After Kiln-Drying, W.L. James, E.T. Choong, D.G. Arganbright, D.K. Doucet, M.R. Gorvad, W.L. Galligan, and W.T. Simpson, 11/12:59-64 (No. 6676).

A New Approach to Calculating Target Sizes, S.J. Wang, 9:53-60 (No. 6654).

Random Sampling Process for Improving Lumber Cut-Up Recovery, K.L. Nowakowski, 11/12:23-24 (No. 6706).

Treated Wood Products

Effect of Fire Retardant Chemicals on Chimney Creosote Deposit, M.M. Nassar and G.D.M. MacKay, 2:53-56 (No. 6542).

Effectiveness of Fumigants Against Marine Wood-Borers, G.G. Helsing, R.D. Graham, and M.A. Newbill, 6:61-64 (No. 6680).

Effects of Post-Treatment Drying Schedule on the Strength of CCA-Treated Southern Pine Dimension Lumber, H.M. Barnes and P.H. Mitchell, 6:29-33 (No. 6617).

Influence of Natural Durability, Laboratory Weathering, Resin Content, and Ammoniacal Copper Arsenate Treatment on the Decay Resistance of African Hardwood Particleboards, S.P.A. Okoro, R.O. Gertjejansen, and D.W. French, 9:41-48 (No. 6381).

Mechanical Tests of Full-Sized Polymer Impregnated Timbers, C.E. Shuler, 6:26-28 (No. 6645).

Observations on Structural Use of Treated Wood in Hawaii, W.W. Wilcox, 6:39-42 (No. 6610).

Treating and Drying Composite Lumber With Waterborne Preservatives: Part I. Short Specimen Testing, L.I. Gaby and L.R. Gjovik, 2:23-26 (No. 6327).

AUTHOR INDEX

A

Ammons, F.L., see Hamilton, J.R.
Arganbright, D.G., see Holmes, S.
Arganbright, D.G., see James, W.L.
Arganbright, D.G., see Lartner, F.L.
Aube, P., see Rose, D.W.

B

Barnes, H.M., and B. Buchanan, Alternate Roofing Materials: Grade, Yield, and Costs for Yellow-poplar and Southern Pine Shingles, 10:48-50 (No. 6700).
Barnes, H.M., and P.H. Mitchell, Effects of Post-Treatment Drying Schedule on the Strength of CCA-Treated Southern Pine Dimension Lumber, 6:29-33 (No. 6617).
Bastendorff, K.M., and A. Polensek, Strength and Stiffness of Red Alder and Bigleaf Maple Pallet Materials, 7/8:51-56 (No. 6489).
Beauregard, M.J., see Bozaan, D.
Binkley, C.S., see Cardellichio, P.A.
Blankenhorn, P.R., see Garges, L.D.
Boone, R.S., High-Temperature Kiln-Drying of 4/4 Lumber From 12 Hardwood Species, 3:10-18 (No. 6584).
Bowyer, J.L., see Leding, D.
Bowyer, J.L., see Stokke, D.D.
Bozaan, D., C.W. Ramm, and M.J. Beauregard, Microcomputer Program for Random Selection of Board Samples From Stacked Lumber, 2:51-52 (No. 6544).
Bozaan, D., see Huber, H.
Bradfield, J., and M.P. Levi, Effect of Species and Wood to Bark Ratio on Pelleting of Southern Woods, 1:61-63 (No. 6554).
Brisbin, R., see Weik, B.R.
Bryant, B.S., see Youngquist, J.A.
Buchanan, B., see Barnes, H.M.
Buongiorno, J., F.M. Huang, and H. Spelter, Forecasting the Price of Lumber and Plywood: Econometric Model Versus Futures Markets, 7/8:13-18 (No. 6670).

C

Cameron, F.A., see Pizzi, A.
Cardellichio, P.A., and C.S. Binkley, Hardwood Lumber Demand in the United States: 1950 to 1980, 2:15-22 (No. 6562).
Carll, C.G., and J.E. Wood, Effect of Chip Freezing on Quality of Ring-Cut Flakes, 4:35-36 (No. 6624).
Cassens, D.L., see Eckelman, C.A.
Cech, F.C., see Hamilton, J.R.
Chi, U.H., see Garbini, J.L.
Choong, E.T., see James, W.L.
Chudnoff, M., W.E. Eslyn, and D.B. McKeever, Decay in Mine Timbers. Part III. Species-Independent Stress Grading, 3:43-50 (No. 6550).
Clark, A., III, and R.H. McAlister, Recovery of Structural Grade Veneer From Four Species of Southern Hardwoods, 6:13-20 (No. 6609).
Conners, R.W., see McMillin, C.W.
Cupp, D.C., see White, M.S.

D

Dean, M.A., and J.H. Kaiserlik, Nondestructive Screening of Hardwood Specialty Blanks, 3:51-56 (No. 6569).
Doucet, D.K., see James, W.L.

E

Eckelman, C.A., and D.L. Cassens, Holding Strength of Metal Inserts in Wood, 6:21-25 (No. 6589).
Eckelman, C.A., and M. Resheidat, Deflection Analysis of Shelves and Case Tops and Bottoms, 6:55-60 (No. 6426).
Ek, A.R., see Rose, D.W.
Ellefson, P.V., Encouraging Growth and Use of Eastern Hardwoods: Public and Private Programs for the Task, 10:18-23 (No. 6755).
Erickson, R.W., H.D. Petersen, and T.D. Larson, Obtaining Uniform Final Moisture Content in the High Temperature Drying of Paper Birch Flitches, 2:27-32 (No. 6516).
Eslyn, W.E., see Chudnoff, M.
Evans, J.W., see Gerhards, C.C.

F

Forrer, J.B., An Electronic System for Monitoring Gradients of Drying Wood, 7/8:34-38 (No. 6647).
French, D.W., see Okoro, S.P.A.
Fritschel, P.R., see Nelson, N.D.

G

Gaby, L.I., and L.R. Gjovik, Treating and Drying Composite Lumber With Waterborne Preservatives: Part I. Short Specimen Testing, 2:23-26 (No. 6327).
Gallisan, W.L., see James, W.L.
Garbini, J.L., M.R. Lembersky, U.H. Chi, and M.T. Hehnen, Merchandiser Design Using Simulation With Graphical Animation, 4:61-68 (No. 6618).
Garcia, J.F., see Hofstrand, A.D.
Garges, L.D., P. Labosky, and P.R. Blankenhorn, Lumber Recovery From Gypsy Moth-Killed Red and White Oak Trees, 7/8:45-50 (No. 6661).
Gerhards, C.C., C.M. Marx, D.W. Green, and J.W. Evans, Effect of Loading Rate on Tensile Strength of Douglas-fir 2 by 6's, 4:23-26 (No. 6593).
Gerhards, C.C., and R.F. Pellerin, Effect of Shock Loading From Series Testing on Tensile Strength of Lumber and Connector Systems, 1:38-43 (No. 6578).
Gertjejansen, R., see Hughes, M.
Gertjejansen, R.O., see Okoro, S.P.A.
Gjovik, L.R., see Gaby, L.I.
Gorvad, M.R., see James, W.L.
Govett, R.L., and S.A. Sinclair, Marketing Research for Primary Processors of Northern Softwood Lumber, 5:13-20 (No. 6629).
Graham, R.D., see Helsing, G.G.
Gramp, G.D., see Groah, W.J.

Green, D.W., see Gerhards, C.C.

Groah, W.J., G.D. Gramp, and M. Trant, Effect of Decorative Vinyl Overlays on Formaldehyde Emissions, 4:27-29 (No. 6602).

Guldin, R.W., Exporting Southern Softwood Lumber: How Small Firms Can Begin, 3:37-42 (No. 6573).

H

Hall, H.J., J.G. Haygreen, and Y.Lee, Minnesota Shear Test Reproducibility and Correlation With Internal Bond, 9:49-52 (No. 6660).

Hamilton, J.R., F.C. Cech, and F.L. Ammons, A Tool for Obtaining Large Cores From Standing Trees, 11/12:33-34 (No. 6679).

Haney, H.L., Jr., see McGee, G.T.

Harris, R.A., Fuel Values of Stems and Branches in White Oak, Yellow-poplar, and Sweetgum, 3:25-26 (No. 6596).

Harris, R.A., and M.A. Taras, Comparison of Moisture Content Distribution, Stress Distribution, and Shrinkage of Red Oak Lumber Dried by a Radio-Frequency/Vacuum Drying Process and a Conventional Kiln, 1:44-54 (No. 6606).

Harris, R.A., M.A. Taras, and J.G. Schroeder, Sound Quality Upholstered Frame Part Yields From Lumber and Green Cuttings Dried by a Radio-Frequency/Vacuum System and by Conventional Kiln-Drying, 7/8:19-21 (No. 6646).

Harris, R.A., and R. Zahner, Wood Fuel Production From Young Piedmont Oak Stands of Sprout Origin, 6:34-38 (No. 6631).

Harris, R.A., see Lee, A.W.C.

Hart, C.A., Relative Humidity, EMC, and Collapse Shrinkage in Wood, 11/12:45-54 (No. 6671).

Hart, C.A., see Kelly, M.W.

Haygreen, J.G., see Hall, H.J.

Hehnen, M.T., see Garbini, J.L.

Helsing, G.G., R.D. Graham, and M.A. Newbill, Effectiveness of Fumigants Against Marine Wood-Borers, 6:61-64 (No. 6680).

Hines, G.A., see Long, R.B.

Hofstrand, A.D., A.A. Moslemi, and J.F. Garcia, Curing Characteristics of Wood Particles From Nine Northern Rocky Mountain Species Mixed With Portland Cement, 2:57-61 (No. 6619).

Hoganson, H.M., see Rose, D.W.

Holmes, S., and D.G. Arganbright, Green Sorting Incense-cedar for Increased Air-Drying Yard Throughput, 3:57-63 (No. 6305).

Hopkins, F.F., see Taylor, F.W.

Huang, F.M., see Buongiorno, J.

Huber, H., R.R. Maeglin, and D. Bozaan, Commercial Evaluation of SDR (Saw-Dry-Rip)--Using Aspen for Door Parts, 11/12:35-39 (No. 6667).

Huber, H.A., see McMillin, C.W.

Hughes, M., and R. Gertjejansen, Spruce Budworm Killed Balsam Fir as a Raw Material for Flakeboard and Waferboard, 2:42-46 (No. 6586).

J

Jahan-Latibari, A., W.E. Johns, and R.V. Subramanian, Technique for Isolating Flakes From the Pressed Mat, 2:33-34 (No. 6530).

James, W.L., E.T. Choong, D.G. Arganbright, D.K. Doucet, M.R. Gorvad, W.L. Galligan, and W.T. Simpson, Moisture Levels and Gradients in Commercial Softwood Dimension Lumber Shortly After Kiln-Drying, 11/12:59-64 (No. 6676).

Johns, W.E., see Jahan-Latibari, A.

Jokerst, R.W., Preheating Veneer Reduces Press Time in Phenolic-Bonded PLV, 2:47-50 (No. 6572).

Jung, J., Investigation of Various End Joints in Parallel-Laminated Veneer, 5:51-55 (No. 6633).

K

Kaiser, H.F., Floating Exchange Rates and the U.S. Forest Products Trade Balance, 11/12:55-58 (No. 6678).

Kaiserlik, J.H., see Dean, M.A.

Kellogg, L.D., see Putnam, N.E.

Kelly, M.W., C.A. Hart, and G.F. Laushinghouse, Water Soak Versus Wicking Test for Hardboard Siding, 6:49-54 (No. 6653).

Krueger, G.P., see Laufenberg, T.L.

L

Labosky, P., see Garges, L.D.

Lanford, B.L., see Somerville, M.C.

Larson, T.D., see Erickson, R.W.

Laufenberg, T.L., R.E. Rowlands, and G.P. Krueger, Economic Feasibility of Synthetic Fiber Reinforced Laminated Veneer Lumber (LVL), 4:15-22 (No. 6604).

Laufenberg, T.L., see Youngquist, J.A.

Laushinghouse, G.F., see Kelly, M.W.

Laytner, F.L., and D.G. Arganbright, Within-Kiln Variability of Transmission Heat Losses, 2:62-68 (No. 6443).

Leding, D., and J.L. Bowyer, Japanese Manufacturing and Management Techniques and the U.S. Forest Products Industry, 11/12:13-22 (No. 6697).

LeDoux, C.B., Cable Yarding Residue After Thinning Young Stands: A Break-Even Simulation, 9:35-40 (No. 6630).

LeDoux, C.B., Production Rates and Costs of Cable Yarding Wood Residue From Clearcut Units, 4:55-60 (No. 6603).

Lee, A.W.C., Physical and Mechanical Properties of Cement Bonded Southern Pine Excelsior Board, 4:30-34 (No. 6634).

Lee, A.W.C., and R.A. Harris, Properties of Red Oak Lumber Dried by Radio-Frequency/Vacuum Process and Dehumidification Process, 5:56-58 (No. 6637).

Lee, Y., see Hall, H.J.

Lemaster, R.L., Saw Blade Tooth Wear Reduction by Electrically Insulating the Saw Blade, 7/8:62-66 (No. 6681).

Lembersky, M.R., see Garbini, J.L.

Levi, M.P., see Bradfield, J.

Lim, Y.T., see Moslemi, A.A.

Little, R.L., Industrial Use of Solar Heat in Lumber Drying: A Long-Term Performance Report, 9:22-26 (No. 6621).
Liu, J.Y., and L.A. Soltis, Lateral Resistance of Nailed Joints--A Test Method, 1:55-60 (No. 6582).
Long, R.B., and G.A. Hines, Analyzing a Forest Resource Based Region Facing Economic Change, 10:51-58 (No. 6607).
Luttrell, L.D., and R.L. Tuomi, Full-Scale Testing and Structural Evaluation of a Truss-Framed Assembly, 1:64-68 (No. 6545).

M

MacKay, G.D.M., see Nassar, M.M.
Maeglin, R.R., see Huber, H.
Marx, C.M., see Gerhards, C.C.
McAlister, R.H., see Clark, A., III.
McCay, T.D., and H.W. Wisdom, Feasibility of Small Mill Investments for Utilizing Small-Diameter Hardwood From Coal Lands in Southwestern Virginia, 6:43-48 (No. 6639).
McGee, G.T., H.L. Haney, Jr., and W.C. Siegel, State Income Tax Implications for Nonindustrial Private Forestry in the United States, 3:27-36 (No. 6592).
McKeever, D.B., see Chudnoff, M.
McMillin, C.W., Evaluating Wood Failure in Plywood Shear by Optical Image Analysis, 7/8:67-69 (No. 6690).
McMillin, C.W., R.W. Conners, and H.A. Huber, ALPS--A Potential New Automated Lumber Processing System, 1:13-20 (No. 6576).
McMillin, C.W., see Taylor, F.W.
McNatt, J.D., Static Bending Properties of Structural Wood-Base Panels: Large-Panel Versus Small-Specimen Tests, 4:50-54 (No. 6632).
McNatt, J.D., see Muszynski, Z.
Mitchell, P.H., see Barnes, H.M.
Morgan, I.L., see Taylor, F.W.
Morselli, M.F., see Sendak, P.E.
Moslemi, A.A., and Y.T. Lim, Compatibility of Southern Hardwoods With Portland Cement, 7/8:22-26 (No. 6588).
Moslemi, A.A., see Hofstrand, A.D.
Mote, C.D., Jr., see Wu, W.Z.
Muszynski, Z., and J.D. McNatt, Investigations on the Use of Spruce Bark in the Manufacture of Particleboard in Poland, 1:28-35 (No. 6579).
Myers, G.E., Effect of Ventilation Rate and Board Loading on Formaldehyde Concentration: A Critical Review of the Literature, 10:59-68 (No. 6655).
Myers, G.E., How Mole Ratio of UF Resin Affects Formaldehyde Emission and Other Properties: A Literature Critique, 5:36-41 (No. 6628).

N

Nassar, M.M. and G.D.M. MacKay, Effect of Fire Retardant Chemicals on Chimney Creosote Deposit, 2:53-56 (No. 6542).

Nelson, N.D., J.A. Sturos, P.R. Fritschel, and L.D. Satter, Ruminant Feedstuff From the Commercial Foliage of Hybrid Poplars Grown Under Intensive Culture, 4:37-44 (No. 6599).
Newbill, M.A., see Helsing, G.G.
Nowakowski, K.L., Random Sampling Process for Improving Lumber Cut-Up Recovery, 11/12:23-24 (No. 6706).

O

Okoro, S.P.A., R.O. Gertjejansen, and D.W. French, Influence of Natural Durability, Laboratory Weathering, Resin Content, and Ammoniacal Copper Arsenate Treatment on the Decay Resistance of African Hardwood Particleboards, 9:41-48 (No. 6381).
Olsen, E.D., see Putnam, N.E.

P

Patterson, D.W., Sawkerf Width Versus Sawtooth Width, 7/8:33 (No. 6668).
Pellerin, R.F., see Gerhards, C.C.
Petersen, H.D., see Erickson, R.W.
Phelps, R.B., Current and Future Demands for Hardwoods, 10:8-11 (No. 6754).
Phelps, R.B., see Spelter, H.
Phillips, D.R., see Schroeder, J.G.
Pizzi, A., and F.A. Cameron, Fast-Set Adhesives for Glulam, 9:61-68 (No. 6571).
Polensek, A., see Bastendorff, K.M.
Putnam, N.E., L.D. Kellogg, and E.D. Olsen, Production Rates and Costs of Whole-Tree, Tree-Length, and Log-Length Skyline Thinning, 6:65-69 (No. 6656).

R

Ramm, C.W., see Bozaan, D.
Resheidat, M., see Eckelman, C.A.
Rhemrev, J., see Szymani, R.
Rose, D.W., A.R. Ek, H.M. Hoganson, and P. Aube, A Spatial Regional Timber Supply Model for Industrial Expansion, 1:21-27 (No. 6486).
Rowlands, R.E., see Laufenberg, T.L.

S

Samson, M., Measuring General Slope of Grain With the Slope-of-Grain Indicator, 7/8:27-32 (No. 6682).
Satter, L.D., see Nelson, N.D.
Schneider, M.H., Domestic-Sized Wood Chip Stoker: Combustion and Efficiency, 3:19-24 (No. 6590).
Schroeder, J., see Weik, B.R.
Schroeder, J.G., and D.R. Phillips, Effect of Sweep and Crook on Veneer Yield, 10:45-47 (No. 6714).
Schroeder, J.G., see Harris, R.A.
Schuman, G.E., and T.A. Sedbrook, Sawmill Wood Residue for Reclaiming Bentonite Spoils, 11/12:65-68 (No. 6721).
Sedbrook, T.A., see Schuman, G.E.
Sendak, P.E., and M.F. Morselli, Reverse Osmosis in the Production of Maple Syrup, 7/8:57-61 (No. 6677).
Shuler, C.E., Mechanical Tests of Full-Sized Polymer Impregnated Timbers, 6:26-28 (No. 6645).
Siegel, W.C., see McGee, G.T.

Simpson, W., Maximum Safe Initial Moisture Content for Press-Drying Oak Lumber Without Honeycomb, 5:47-50 (No. 6622).
Simpson, W.T., and J.L. Tschernitz, Solar Dry Kiln for Tropical Latitudes, 5:25-34 (No. 6580).
Simpson, W.T., see James, W.L.
Sinclair, S.A., see Govett, R.L.
Soltis, L.A., see Liu, J.Y.
Somerville, M.C., B.L. Lanford, and B.J. Stokes, Mechanized Piling During Pine Plantation Thinning, 4:45-49 (No. 6605).
Spelter, H., and R.B. Phelps, Changes in Postwar U.S. Lumber Consumption Patterns, 2:35-41 (No. 6585).
Spelter, H., see Buonsiorno, J.
Stewart, H.A., Resultant Force and Surface Quality From Some Face-Milling Variables, 5:21-24 (No. 6601).
Stokes, B.J., see Somerville, M.C.
Stokke, D.D., and J.L. Bowyer, Face-Glued Blockboard From Plywood End Trim, 11/12:40-44 (No. 6687).
Stolley, J.S., How a Forest Products Firm Looks at Eastern Hardwood Opportunities, 10:13-16 (No. 6756).
Sturos, J.A., see Nelson, N.D.
Subramanian, R.V., see Jahan-Latibari, A.
Szymani, R., and J. Rhemrev, Latest Developments in Circular Saw Tensioning, 5:64-68 (No. 6683).

T

Taras, M.A., see Harris, R.A.
Taylor, F.W., F.G. Wagner, Jr., C.W. McMillin, I.L. Morgan, and F.F. Hopkins, Locating Knots by Industrial Tomography--A Feasibility Study, 5:42-46 (No. 6638).
Trant, M., see Groah, W.J.
Tschernitz, J.L., see Simpson, W.T.
Tuomi, R.L., see Luttrell, L.D.

V

Vick, C.B., An Emulsion Polymer/Isocyanate Adhesive for Laminating Composite Lumber, 9:27-34 (No. 6598).
Vick, C.B., Hydrolytic Effects of an Acid-Phenolic Molding Resin on Southern Pine, Red Oak, and Douglas-fir, 10:37-44 (No. 6666).
Vodak, M.C., see White, M.S.

W

Wagner, F.G., Jr., see Taylor, F.W.
Wang, S.J., A New Approach to Calculating Target Sizes, 9:53-60 (No. 6654).
Weik, B.R., E.M. Wengert, J. Schroeder, and R. Brisbin, Practical Drying Techniques for Yellow-poplar S-D-R Flitches, 7/8:39-44 (6686).
Wengert, E.M., see Weik, B.R.
White, M.S., M.C. Vodak, and D.C. Cupp, Effect of Surface Compaction on the Moisture Content of Piled Green Hardwood Chips, 5:59-60 (No. 6620).
Wilcox, W.W., Observations on Structural Use of Treated Wood in Hawaii, 6:39-42 (No. 6610).
Winandy, J.E., Evaluation of Live Oak Submerged Underwater for 50 Years and Proposed for Use in Rebuilding the U.S.S. Constitution, 5:61-63 (No. 6636).
Wisdom, H.W., see McCay, T.D.
Wood, J.E., see Carll, C.G.
Wu, W.Z., and C.D. Mote, Jr., Analysis of Vibration in a Bandsaw System, 9:12-21 (No. 6745).

Y

Youngquist, J.A., T.L. Laufenberg, and B.S. Bryant, End Jointing of Laminated Veneer Lumber for Structural Use, 11/12:25-32 (No. 6664).

Z

Zahner, R., see Harris, R.A.